



AUGUSTA  
OFFSHORE



# AHTS ASSO VENTOTTO

Year	2007
Flag	Italian
Builder	Kleven Maritime - Myklebust - Norway
Design	UT 734
Class society	RINA
Class notation	+Hull, +Mach; Tug; Supply Vessel; DP1, FiFi1, Water-Spraying, Oil Recovery Ship; Nav IL; Aut-UMS, inwatersurvey
IMO number	9379416



GENERAL INFO	
Year	2007
Flag	Italian
Builder	Kleven Maritime - Myklebust - Norway
Design	UT 734
Class society	RINA
Class notation	+Hull, +Mach; Tug; Supply Vessel; DP1, FiFi1, Water-Spraying, Oil Recovery Ship; Nav IL; Aut-UMS, inwatersurvey
IMO number	9379416

MAIN PARTICULARS	
Length OA	68,90 mt
DWT	2.450 T
Length BPP	60,45 mt
Breadth moulded	16,80 mt
Depth moulded	7,20 mt
Gross tonnage	2.554 T
Net tonnage	766 T
Maximum draft	6,15 mt

CARGO CAPACITIES	
Working Clear Deck - space	480 sqm
Working Clear Deck - length x breadth	31,5mt x 14mt
Max Deck Cargo	1.000 T
Deck loading	10T/sqm from stern roller to frame 7 x 8mt wide - 7T/sqm from frame 7 to frame 24 x 6mt wide - 5T/sqm wooden planking
Fuel Oil	756 cbm
Fresh Water	731 cbm
Drill Water	multipurpose - 1.047 cbm
Brine	multipurpose - 535 cbm
Mud	multipurpose - 535 cbm
Base Oil	dual purpose - 202 cbm
Dry Bulk	247 cbm
Number of Dry Bulk tanks	4

MACHINERY/PROPULSION	
Bollard pull continuous	137 T
Main Engines	2 x Bergen 33L6P 1.800 kW each 2 x Bergen 33L8P 2.400 kW each
Drive type (Direct/Diesel Electric)	Direct
Total power (BHP)	11.400
Rudders	Two off Ulstein High Lift Flap. Two independent electric-hydraulic steering gears
Bow thruster(s) (number and BHP)	2 x tunnel Ulstein TT 1650 - 900 BHP (V controllable pitch propellers)
Stern thruster(s) (number and BHP)	1 x tunnel Ulstein TT 1650 - 900 BHP (V controllable pitch propellers)
Shaft generator	2 x 2.400 kW - 440V - 60HZ
Diesel generator	2 x Volvo Penta 350kW - 440V - 60HZ
Emergency generator	1 x Volvo Penta 160kW - 440V - 60HZ
Fuel type - (MGO / IFO / HFO)	MGO

ANCHOR HANDLING CAPACITIES	
Winch Type - Double/Triple Drum	Brattvaag BSL 350W/SL350W - Double Drum waterfall
Winch - Pull Rating	350 (first line pull) T
Winch - Brake Rating	450 T
Anchor Handling Drum(s) wire capacity	2.540mt x 76mm
Towing Drum wire capacity	3.800mt x 76mm
Work wire A/H - length / diameter	800mt x 76mm + dead man 200mt
Tow wire - length / diameter	1.200mt x 76mm - break load 437 T
Spare tow wire - length / diameter	1.200mt x 76mm - break load 437 T
Tugger Winch (number / capacity / rating)	2 x 15T x 30 mt/min

Capstan	2 x 10T x 20 mt/min
Rig chain lifters (Gypsies)	2 x 76 mm / 2 x 94 mm

DECK EQUIPMENT	
Chain lockers	220 cbm
Stern Roller	5mt x 3mt diam - 500 T/SWL
Towing Pins (type and number)	2 off pair R.R.M. - 250 T/SWL
Shark Jaws - (type and number)	2 x Rolls Royce Karm fork, variable inserts and hydraulic centering device
Crane	3 T / 16mt

CARGO DISCHARGE CAPACITY	
Fuel Oil	200 cbm/hr at 9 bar
Drill Water	200 cbm/hr at 9 bar
Brine	75 cbm/hr at 18 bar
Mud	75 cbm/hr at 18 bar
Base Oil	100 cbm/hr at 9 bar

SPEED/CONSUMPTION	
Max Speed/Consumption	15,5 knots per 32 T/day
Economical Speed/Consumption	10 knots per 12 T/day
Port Consumption	0,5 T/day

ACCOMODATION	
Crew	12 single bed cabins + 3 double bed cabins (all cabins have private bathroom)
Passengers	2 four bed cabins (private bathroom)
Hospital	1

FI-FI	
FiFi	FiFi1
Number of monitors	2 x 1.200 cbm/hr
Number of pumps	2 x 1.800 cbm/hr

ANTI POLLUTION EQUIPMENT	
Dispersant	10 cbm
Oil Recovery capacity	not dedicated - 606 cbm

RESCUE EQUIPMENT	
Rescue Zone	Yes
Rescue Boat	1 x 6persons - 530 MIDGET MK II - 75HP
Inflatable life rafts	6 - 96 persons in total
Life jackets	41 (including 2 x children)

NAVIGATION AND COMMUNICATION EQUIPMENT	
Joystick (Yes / No)	Yes
DP	Class1
Radar (number and type)	2 x Baybridge X band and S band
GMDSS	3 x Jotron TR 20
Inmarsat	2 x Thrane&Thrane TT-3042C + 1 x Thrane&Thrane Fleet F77
VHF	2 x Thrane&Thrane RT 5022
DGPS/GPS	2 x DGPS Kongsberg DPS 200 and DPS 132 + Leica GPS MX 420
Echo sounder	Sperry ES 5100
Speed log	Yes
Gyroscopic compass	3 x Sperry Navigat X MK 1
Automation	Sperry Navipilot V HSC