

GENERAL

CLASSIFICATION

YARD NUMBER 5130 28-31 BASIC FUNCTIONS

Towing, mooring, escorting and Ø fire-fighting operations

Lloyd's Register

¥ 100 A1 Escort Tug [¥] LMC UMS

IWS

Ø Lloyd's Register

▼ 100 A1 Escort Tug [♣] LMC UMS

IWS Fire Fighting Sh  $\,$  ip 1 with

waterspray

**DIMENSIONS** 

LENGTH O.A. 32.44 m BEAM O.A. 13.29 m DEPTH AT SIDES 5.50 m DRAUGHT AFT 6.30 m

DISPLACEMENT (%98 CONSUMABLES) 950 ton (approx.)

**TANK CAPACITIES** 

FUEL OIL 200 m<sup>3</sup> FRESH WATER  $65.2 \text{ m}^3$  $10.7 \, \text{m}^{\,3}$ LUBRICATION OIL 4.9 m<sup>3</sup> DIRTY OIL  $4.9 \text{ m}^3$ BILGE WATER SLUDGE  $2.4 \text{ m}^{3}$ Ø FOAM 14.3 m<sup>3</sup> Ø DISPERSANT  $3.0 \text{ m}^{3}$ SEWAGE

PERFORMANCES

BOLLARD PULL AHEAD 87.5 ton BOLLARD PULL ASTERN 80.0 ton SPEED AHEAD 14.2 knots

**PROPULSION SYSTEM** 

MAIN ENGINE 2x Upgraded Caterpillar C280-8/MC1 MAIN ENGINE POWER 5966 bkW (8000 bhp) at 1010 rpm AZIMUTH THRUSTERS 2x Rolls Royce US 2 85 CP 3000 mm controllable pitch propellers PROPELLERS ALARM SYSTEM Praxis M ega guard FORCED VENTILATION 40.000 m 3/hr

2.3 m<sup>3</sup>

AUXILIARY EQUIPMENT MAIN GENERATOR SETS

BILGE PUMPS BILGE STRIPPING PUMP FUEL PUMPS FUEL PUR IFIERS COOLING SYSTEM SEWAGE TREATMENT PLA FRESH WATER PRESSURE HYDRAULIC SYSTEM

Ø DISPERSANT Ø FIRE FIGHTING

Ø FIFI MONITORS

DECK LAY -OUT ANCHORS + CHAIN ANCHOR/TOWING WINCH

CAPSTAN Ø DECK CRANE Ø TOW ING WINCH AFT

TOWING HOOK AFT STERN ROLLER Ø RESCUE BOAT

GPS

NAVTEX

M.E. driven pum s, 1x1200m <sup>3</sup>/hr, 2x1200m <sup>3</sup>/hr(FiFi1) 2 x 1200 m <sup>3</sup>/hr, water/foam 2 x 585 kg Pool ( HHP), tot. 330m, chain 24mm, U2

"YN 5130 28-31"

R40/35

2x Caterpillar C9TA, 400/230V, 188 kVA, 50 Hz

Box cooling + anti marine growth system

Dispersant pump set with 2 spraybooms

Sterling SIHI AKHA 5101 and 2x

Double main engine driven pumps

2x Westfalia OTC 2 -02-137

Hamann, Supermini+

2x Sterling AOHA 3101

2x Sterling SIHI AKHA 34 6101 m<sup>3</sup>/hr at 10 m.w.g.

Sterling SIHI AOHA 4.5 3101 m<sup>3</sup>/hr at 10 m.w.g.

Hydraulically driven two speed winch with double drum and warping head, pull 50 ton at 12 m/min. and speed up to 32 m/min, 2x 150 m. Ø 96 mm. slack rope 212 ton brake

5 ton at 15 m/min. Electrically driven Heila HLM 10 -2S 1100 kg at 7.84 m

Hydraulically driven, two speed winch with spooling device, pull 50,0 ton at 12 m/min and at 32 m/min,

1000 m Ø 60 mm wire, 2 12 ton brake Mampaey 100 0 kN 101.9 ton S.W.L. SWL 126 ton, length: 3.0 m diam.: 1.2 4 meter inflatable with 25 hp outboard engine

ACCOMMODATION

For 10 persons, insulated and finished with durable mo dern linings, floating floors, acoustical ceiling in the wheelhouse and air -conditioned. With 6 cabins, galley, mess/dayr oom and sanitary facilities.

NAUTICAL AND COMMUNI SEARCHLIGHT **CATION EQUIPMENT** 2x Pesch , 1000 W, 230 V RADAR SYSTEM Furuno FAR -2117

COMPASS /AUTOPILOT Magnetic Kotter / Simrad AP -70 Furuno GP -150 ECHOSOUNDER / SPEED LOG

Furuno FE -700 / Furuno DS -80 VHF RADIO TELEPHONE 2x Sailor Compact 6222 (one with DSC)


Furuno NX -700


AIS / Ø SSB Furuno FA -150 / Ø Furuno F S-1575 EPIRB / SART Jotron Tron -4OS / Jotron Tron Sart


Ø AN EMOMETER Ø Windsonic OMC 115 2x Furuno Felcom 18,1x with LRIT INMARSAT


COMPLETE VESSEL ON STOCK


\* PHOTOGRAPH SHOWS SIMILAR VESSEL / Ø = OPTIONAL EQUIPMENT











## DAMEN ASD TUG® 3213 "YN 513028-31"



DAMEN SHIPYARDS GORINCHEM

Member of the DAMEN SHIPYARDS GROUP



Industrieterrein Avelingen West 20 4202 MS Gorinchem P.O. Box 1 4200 AA Gorinchem The Netherlands phone +31 (0)183 63 99 11 fax +31 (0)183 63 21 89

info@damen.com www.damen.com